



TEKNİK ÖZELLİKLERİ

MODEL	TRX-CS160	TRX-CS250	TRX-CS360	TRX-CS400	TRX-CS450	TRX-CS550	TRX-CS560	TRX-CS610	TRX-CS660	TRX-CS710	
SİLİNDİR ÇAPI MM	160	250	360	400	450	550	560-510	610	660	710	
SİLİNDİR UZUNLUĞU MM	320	620	900	1000	1200	1500	1530	1930	2130	2200	
ÖN SİLİNDİR DÖNÜŞ HIZI m/min	9	16.3	17.7	19.4	21.8	22.5	27.3	27.3	28	31.9	
ARKA SİLİNDİR DÖNÜŞ HIZI m/min	--	--	--	21.9	25.6	31.7	--	31	31.6 / 30.5	30.26	
ÖN VE ARKA SİLİNDİR ORANI	1:1.35	1:1.1	1:1.25	1:1.27 / 1:1.08	1:1.27 / 1:1.08	1:1.2 / 1:1.09	1:1.26	1:1.26 / 1:1.09	1:1.24 / 1:1.09 / 1:1.13	1:1.51 / 1:1.09	
İKİ SİLİNDİR ARASI MESAFE MM	4.5	8	10	10	12	16	15	15	15	15	
KAPASİTE (BESLEME MİKTARI) KG	1.2	10-15	20-25	30-35	50	65-70	65-70	140	165	190	
ELEKTRİK MOTORU KW	5.5	18.5	30	45	55	110	90	160	185 / 250	280	
MAKİNA ÖLÇÜLERİ	L	1133	2722	4200	4471	5405	6646	6270	6575	7280	8185
	W	920	1115	1780	1850	1740	2736	2282	2910	3400	3910
	H	1394	1345	1760	1855	1790	2105	2000	1800	2530	2270
MAKİNA AĞIRLIĞI (TON)	2	3.2	6.5	8.6	10.3	22	19.4	44	49	59	