# C20 Chain actuator Thrust force 300 N Max stroke 360 mm



## PRODUCT DESCRIPTION

Electric C20 actuator with double link articulated chain, enclosed in a suitable casing, with different mounting accessories for top and bottom hung windows. Operation at 230V 50Hz or, as an alternative, at 24V DC. Maximum applicable load 300N. Fast hooking and unhooking system of the chain to the window. Adjustment of the force and of the stroke at 240 or 360mm by external knobs (for C20 tandem 360mm fixed stroke, special stroke optional on request). Electronic end of stroke in closing by current absorption control. CE marked device.














Double link chain with very high resistance on heavy loads.



Long stroke, together with a slim and attractive housing, to allow applications that require minimum size (International patent on the chain path).




Stroke-end by amperometric absorption in closing to avoid chain adjustments in closing and any possible installation mistake.



### **TECHNICAL SPECIFICATIONS** C20 230V C20 24V

Power supply voltage	230V ~ 50Hz	min 21V ~ max 28V d.c.
Max applicable load in thrust	300 N	300 N
Max applicable load in traction	200N	200 N
Stroke	240 and 360 mm	240 and 360 mm
Absorbed current	0,12 A	0,43 A
Idle translation speed	8 mm/s	7,5 mm/s
Duration of the idle stroke	46 s	48s
Double insulated	YES	YES
Service type	S2 of 4 min	S2 of 4 min
Operating temperature	- 5°C + 50°C	- 5°C + 50°C
Protection Class	IP 30	IP 30
Stroke end regulation in closing	not necessary	not necessary
Parallel connection option	YES	YES
Stroke end	Electronic in opening, by ampe	erometric absorption in closing
Dimensions	362 x 34 x 48 mm	362 x 34 x 48 mm
Weight	0,970 kg	0,940 kg



## C20 standard 1 push point

	Programme Programme Company
3A3#	C20 chain actuator 230V - black
3A3#	C20 chain actuator 230V - grey
3A3#	C20 chain actuator 230V - white
3A3#	C20 chain actuator 24V - black
3A3#	C20 chain actuator 24V - grey
3A3#	C20 chain actuator 24V - white

## TANDEM

# C20 Tandem standard 2 push points on the same window frame (360mm stroke)

3A7#	Kit C20 chain actuator - tandem version - 230V black
3A7#	Kit C20 chain actuator - tandem version - 230V grey
3A7#	Kit C20 chain actuator - tandem version - 230V white
3A7#	Kit C20 chain actuator - tandem version - 24V black
3A7#	Kit C20 chain actuator - tandem version - 24V grey
3A7#	Kit C20 chain actuator - tandem version - 24V white

## Description of the standard pattern for 1 push point

3A3# C20 chain actuator 230V 1,5mt lead

Frontal swivel brackets set for top/bottom hung windows

Upper bracket for bottom hung windows ARS Rapid hooking device to the frame

Spare parts

### Description of the standard pattern for 2 push points


3A7# C20 chain actuator - tandem version - 24V (2 pcs) 6mt lead

AL2/SW 230V to 24V transformer unit

Frontal swivel brackets set for top/bottom hung windows (2 pcs)

Upper bracket for bottom hung windows (2 pcs)
ARS Rapid hooking device to the window frame (2 pcs)

Spare parts (2 pcs)



## Accessories and spare parts

3A3200	Frontal swivel brackets set for top/bottom hung windows - black
3A3202	Frontal swivel brackets set for top/bottom hung windows - grey
3A3201	Frontal swivel brackets set for top/bottom hung windows - white
3A3210	Swivel brackets set for vertical mounting - black
3A3212	Swivel brackets set for vertical mounting - grey
3A3211	Swivel brackets set for vertical mounting - white
3A3501	Brackets set for installation on the moving part of the window - black
3A3503	Brackets set for installation on the moving part of the window - grey
3A3502	Brackets set for installation on the moving part of the window - white
1A3640	Upper bracket for bottom hung windows - black
1A3642	Upper bracket for bottom hung windows - grey
1A3641	Upper bracket for bottom hung windows - white
1UA001	ARS Rapid hooking device to the window frame - black
1UA003	ARS Rapid hooking device to the window frame - grey
1UA002	ARS Rapid hooking device to the window frame - white
3A3000	Standard spare parts

